





Decking Comparison Chart

More information available online @ www.tsfpi.com

| |  EverGrain <small>COMPOSITE LUMBER</small> |  Envision <small>COMPOSITE LUMBER</small> TAMKO |
|---|---|---|
| PLASTIC TYPE | HDPE | HDPE |
| WOOD TYPE | pine base | pine base |
| % OF WOOD TO PLASTIC | 50/50 | 50/50 |
| USES RECYCLED MATERIAL | yes | yes |
| NUMBER OF COLORS | 5 (stock all) | 4 (stock all) |
| DECKING OPTIONS | 5/4x6-12', 16', 20' | 5/4x6-12', 16', 20' |
| DECKING SPAN RESIDENTIAL <small>(NON-DIAGONAL)</small> | 17" o.c. max | 17" o.c. max |
| DECKING SPAN COMMERCIAL <small>(NON-DIAGONAL)</small> | 12" o.c. max | 12" o.c. max |
| DECKING SPAN DIAGONAL <small>(RESIDENTIAL)</small> | 12" o.c. max | 12" o.c. max |
| RAILING SYSTEM | Tam-Rail Vinyl and Marquee Composite | complimentary color Marquee Railing System |
| FASCIA/SKIRTING | 1/2"x11-7/8"x12' | 7/16"x12"x12' |
| END SPACE OF DECKING BETWEEN BOARD | 1/16" per 20° under high <small>(see full detail in installation instructions)</small> | 1/16" per 20° under high <small>(see full detail in installation instructions)</small> |
| EDGE SPACING OF DECKING BETWEEN BOARDS | 1/8" min | 1/8" min |
| DISTANCE OF FASTENER FROM EDGE OF BOARD | 1" min | 1" min |
| DISTANCE OF FASTENER FROM END OF BOARD | 3/4" min (pre-drill) | 3/4" min (pre-drill) |
| FASTENER TYPE SUGGESTED | E.G. 123 Hidden Fastener -or- #8 x 2-1/2" deck screw - or CAMO <small>(see full detail installation)</small> | TC-G Hidden Fastener - or Envision Deck Screw (color match) - or CAMO <small>(see full detail installation)</small> |
| FIRE RATING | <200 using ASTM E84 | <200 using ASTM E85 |
| WARRANTY | 20 yr. limited 5 yr. full start period | 20 year limited on product 5 yr. full start period 20 year limited on stain resistance |
| WEBSITE | www.tamko.com | www.tamko.com |

information on this document is subject to change without notice.