



Epilay™ ProtecTite™ Superior Roofing Underlayment with its advanced engineering is highly recommended for mechanically attached, coated woven synthetic roofing underlayment for sloped roofs. ProtecTite™ Superior will meet and exceed ASTM D4869 and D226 ratings. ProtecTite™ Superior is specifically manufactured to replace the 15# & 30# traditional felt paper.

ProtecTite™ Superior's GripWalk™ unique gray top layer which provides for a cooler working surface can be used under primary roofing materials to replace 15# felt. GripWalk™ high traction walking surface permits easier steep slope walk-ability, even during high condensation or moisture on the surface.

ProtecTite™ Superior's Skid-Resist™ anti-skid bottom surface made with advanced polymers helps keep the underlayment intact and prevents the fabric from tearing while it is being fastened avoiding any leakages through the underlayment layer.

ProtecTite™ Superior is 25 times stronger than 15 # felt and 4x lighter than 15# felt. With a 7mil thickness, a 10 square roll weighs only 23 lbs.! This super low weight combined with 48" width and 250 ft. run length means big savings in time and labor - over 30% faster to install than felt!. These unique design features, when coupled with ProtecTite™ Superior's exceptional light weight and exceptional tear strength, allows the contractor to easily carry the roll up and down the ladder. Fewer laps, cuts, and roll handling means you can do more jobs in less time resulting in huge savings for you, the roofing contractor.

ProtecTite™ Superior is an acceptable underlayment product for metal roofing as well as traditional shingles.

Epilay™ Superior is 100% synthetic composition providing the following benefits to the roofing contractor:

- 1 year UV protection
- Water repellant, non-absorbent
- 7 mil thickness
- Works best for use under Asphalt shingles & metal roofing
- Does not wrinkle, crack or become stiff in colder temperatures for smooth and easy installation
- Epilay™ Superior will not dry out or leach oil in high heat environments as organically saturated felts do
- 4 times lighter and 25 times stronger than 15# felt
- 15 year limited warranty
- Class A Fire ASTM E108—meets & exceeds ASTM D4869 and D226
- Synthetic construction impervious to mold growth
- Superior 4 ply underlayment (3 ply cross-woven coated polypropylene with a layer of non-woven polypropylene)
- Strong and durable polymer construction
- 100% recyclable
- Temperature performance range -40°F to 240°F

