

Can Designer and Soar Signature be installed horizontal or vertical?

Yes!

Can you use traditional window/door trims or are Sylvanix trims always required?

In most cases, Sylvanix trims will be required for the best appearance in many situations; however, using traditional window/door/transition trims are fine to use with Sylvanix cladding.

Can Soar Signature trims be used vertical or horizontal?

Yes. Trims labeled horizontal simply have more coverage for horizontal cladding movement but can be used for vertical applications as well.

What is Sylvanix made out of?

HDPE (milk bottles, grocery bags, etc...) & eucalyptus hardwood.

Does Sylvanix expand & contract?

YES, as with all materials, there is thermal expansion & contraction. Sylvanix has a smaller amount of movement compared to most other composites.

What is the warranty?

Sylvanix carries a 25-year stain, fade, rot, warp, split & splinter ltd warranty.

Is there a fire rating?

Sylvanix carries a class C fire rating

Are the cut ends required to be sealed or coated?

No!

What are the primary benefits to Sylvanix when it relates to longevity?

Easy to clean, moisture & rot resistant, termite & pest resistant, no painting/staining, fade resistant, no splinters, cracks, or warping

What is the exposure dimensions (for figuring sqft & coverage)?

Soar Signature 5-1/2", Designer 6"

Are furring strips required for installation?

For horizontal applications furring strips are not required as long as fasteners hit studs no more than 16" on center. For vertical installation furring strips are required since hitting a stud cannot be achieved on most pieces. Furring strips need to be fastened to studs no more than 16" on center.

Why are there two lengths of color match face screws?

The 1-7/8" are for face screw situations going into furring strips (common for vertical cladding installations). The 2-1/2" are for face screw situations going into studs (common for horizontal situations and/or where furring strips are not used. The screw would need to be longer to go through trim or cladding, through sheathing and into a stud).

What are the rubber supports for?

Rubber supports are for starting and/or ending siding installation where a clip isn't present to set the proper space off the wall.

NOTE: two options of supports are available for Soar Signature. Refer to installation manual for specific information.

Can Sylvanix cladding be used in horizontal plane situations such as decking?

Sylvanix cladding cannot be used for decking/walking surfaces but it can be used for ceiling/soffit applications.

Is there a builder rebate?

Yes, builders & contractors can receive \$50 for every \$1,000 purchase of Sylvanix products up to \$500. This is for first-Time users.