



- ▶ Air Resistive Barrier
- ▶ Water Resistive Barrier
- ▶ Vapor Permeable
- ▶ Durable



Tri-Shield Housewrap is the most effective synthetic material to stop wind from robbing homes of insulation and energy values. Tri-Shield Housewrap is a lightweight product which cuts down on installation time. Our housewrap prevents rain from getting into the wall assembly while tiny perforations check moisture in the form of condensation, allowing water vapor to escape to the outside.

Tri-Shield Housewrap is manufactured in widths ranging from 3' to 10' and roll lengths of 100', 150' and 195'.

Trapezoidal Tear—Warp 30 lbs Fill 19 lbs
test method—ASTM 4533

Tensile Strength—Warp 68 lbs Fill 44lbs
test method—ASTM D 5034

Weight—1.92 oz/sq.yd (+/- 5%)
test method—ASTM D 751

Water Resistance—Pass
test method—ASTM 779

AATCC 16 Part 3 Light Resistance (UV)
100, 200, 300 hours—

No Degradation or Loss of Strength

Water Vapor Transmission—
12-15 perm test method—ASTM E 96A

Material—Woven
Polypropylene

Thickness—
Avg. 5.0 mils

**6 MONTH UV
EXPOSURE
RATING**



tsfpi.com

Note: It is the responsibility of the buyer to independently certify the housewrap for their own specific application.

- Edwardsburg, MI (888) 663-8419
- Gaylord, MI (855) 367-4477
- Grand Rapids, MI (877) 369-8469
- Indianapolis, IN (800) 256-8152
- Lexington, KY (800) 788-8865
- Milan, TN (844) 686-8931
- Saginaw, MI (877) 755-7122
- Springfield, OH (800) 949-6325
- Toledo, OH (866) 216-9025